



# GORE® Filtration Products

HIGH DURABILITY FILTER BAG

Polytetrafluoroethylene Felt  
830 g/m<sup>2</sup> (24.5 oz/yd<sup>2</sup>)

## DESCRIPTION

A 260 °C (500 °F) maximum service temperature, polytetrafluoroethylene felt filter bag for use in pulse jet style dust collectors with chemically aggressive operating conditions.

## FEATURES & BENEFITS

- Patented GORE™ High Durability membrane technology provides an excellent combination of filtration efficiency, airflow, and durability.
- Chemically inert providing the highest all-around chemical resistance and maximum bag life.
- Constructed using a woven PTFE scrim that provides excellent dimensional stability, extended flex life, and resistance to mechanical damage over the life of the filter.

## APPLICATIONS

- **Chemicals Processing:** Chemical process reactors that incorporate micronizing, grinding, and product collection in extreme environments that are chemically and thermally aggressive.
- **Minerals Processing:** Brick kilns.
- **Metals Industry:** Lead, copper, and other base metal production.
- **Power Generation and Incineration:** Medical and municipal waste incineration, as well as coal-fired boilers.

## LAMINATE TECHNICAL DATA

Weight	830 g/m <sup>2</sup> (24.5 oz/yd <sup>2</sup> )
Fiber Content	Staple – Polytetrafluoroethylene Scrim – Woven Polytetrafluoroethylene
Felt Construction	Supported Needlefelt
Continuous Operating Temperature	260 °C (500 °F)
Maximum Surge Temperature	274 °C (525 °F)
Acid Resistance	Excellent
Alkali Resistance	Excellent
Breaking Strength	
• Warp	890 N/5 cm (200 lb/2 in) wide sample
• Fill	824 N/5 cm (185 lb/2 in) wide sample
Mullen Burst	4136 kPa (600 psi)
Thickness	1.07 mm (0.042 in)
Thermal Stability	< 2 % shrinkage at 260 °C (500 °F) after 2 hours (unrestrained)
Durability	Very good

**Note:** All data expressed as typical values. This technical data is subject to change. Please contact W. L. Gore & Associates, Inc., directly to confirm current information.

FOR INDUSTRIAL USE ONLY. Not for use in food, drug, cosmetic or medical device manufacturing, processing, or packaging options.

GORE and designs are trademarks of W. L. Gore & Associates © 2011–2019 W. L. Gore & Associates, Inc.

### W. L. Gore & Associates, Inc.

101 Lewisville Road, Elkton, MD 21921

US Toll-Free: 800.437.5427 • Phone: +1.410.506.3560

Fax: +1.410.506.0107 • E-mail: filterbags@wlgore.com

[gore.com/filterbags](http://gore.com/filterbags)

